




Flexible Twistable Waveguide

P/N: FT-84/1200-KF.KF-B.NP

DATASHEET



Part Number:

Description

Product Type:

Waveguide Size:

Flange 1:

Flange 2:

Length:

Flange Material / Finish:

Accessories:

Mechanical Specifications

Jacket Material:

Core Material:

Max. Recommended Operating Pressure:

Min E-Plane Bend Radius (Static):

Min H-Plane Bend Radius (Static):

Maximum Twist (Static):

Min E-Plane Bend Radius (Repeated):

Min H-Plane Bend Radius (Repeated):

Maximum Twist (Repeated):

Electrical Specifications

Frequency Range: 7.05 - 10.0 GHz

Insertion Loss: 0.36 dB Maximum

Return Loss: 25.1 dB Minimum

Peak Power: 330 kW Maximum

Average (CW) Power: 1.5 kW Maximum

Contact Information

DVB-Tech S.r.l.

Via Magenta 2/B

20010 Inveruno

Milan, ITALY

Phone:

Fax:

E-mail:

Web:

+39 0294 750074

+39 0297 250482

sales@dvb-tech.com

www.dvb-tech.com

FT-84/1200-KF.KF-B.NP

Flexible Twistable Waveguide

R84 / WG15 / WR112

KF (UG 52B/U)

KF (UG 52B/U)

1200 mm / 47.2 inches +/- 1.5% or +/- 2 mm

Brass Flanges / Nickel Plating & External Black Paint

Screws, Nuts, Washers, O-ring(s) / Gasket(s)

Silicone Rubber

Silver Plated Brass

10 psi / 1 kg/cm²

82 mm / 3.2 inches

164 mm / 6.5 inches

260 Deg/m or 79.2 Deg/ft

328 mm / 12.9 inches

656 mm / 25.8 inches

68 Deg/m or 20.7 Deg/ft

Environmental Performance

Temperature Range: -70 to +150°C

UV Resistance: Excellent

Ozone Resistance: Excellent

I.P. Rating: IP68

Salt Mist: BS EN 60068-2-52

(method Kb) - Extreme

Marine Environments